
 0338-CPD-1002	EN 14041:2004 	Manufactured by: Tarkett Ltd Lenham, Maidstone Kent ME17 20X UNITED KINGDOM
	EN 13845 Safetred Universal	

TECHNICAL DATA	STANDARDS	PROPERTIES
Classification	EN 685 Commercial Industrial EN 13845	Classes: 34 43 ES _r
Total thickness	EN 428	2.0mm
Total weight	EN 430	3 170 g/m ²
Safety Clean PUR reinforcement		Yes
Abrasion	EN 13845	< 10% particle loss
Residual indentation	EN 433	< 0.10mm
Furniture Leg	EN 424	No damage
Castor Chair	EN 425	No damage
Dimensional stability	EN 434	< 0.10%
Curl resistant to heat	EN 434	≤ 1mm
Reaction to fire	EN 13501-1 EN ISO 9239-1 IMO A653	B _f s1 with acrylic adhesive on wood > 8 kW/m ² Pass
Slip resistance	TRRL Pendulum 45 (Wet) Surface Roughness DIN 51130 DIN51097	>36 > 20 μm R10 A
Electrostatic properties	EN 1815 EN 1081	< 2kV on concrete > 10 ¹⁰ ohms
Impact sound reduction	EN ISO 140-8 EN ISO 717/2 ΔL _w	ΔL _w = 4dB
Acoustic improvement	NF S 31-074	L _{n,e,w} = 75dB
Light fastness	EN ISO 105-B02	7
Chemical resistance	EN 423	Good resistance to everyday substances
Anti Fungal Treatment		Incorporates a biostat to resist fungal and bacterial growth
Thermal resistance Underfloor heating	EN 12524 DIN 52612	0.01 m ² K/W Suitable provided that the surface of the subfloor does not exceed 27°C
Colours		16
Form of delivery	EN 426	Rolls: 20 lm x 2 m